

2. Professional Washer Extractor/Professional Dryers

FW60, FD112, FDC112, FDHP112

Features and Benefits

Washer Extractors

- White painted panels
- Stainless steel drum and tub
- Easy to use timer mop and medical programmes
- Soap hopper at the front
- Matching dryer available space saving when placed on top

Drvers

- White painted panels
- Stainless steel drum and tub
- Large door opening (Ø45cm)



Options

Washer Extractors

- Drain valve
- Liquid soap pumps
- Marine voltages available

Dryers

- Condens unit (FDC112)
- Heat pump model (FDHP112)
- Marine voltages available





TYPE		FW60		
		FW6U		
CAPACITY				
Drum capacity	kg/lb	6/13		
Drum volume	litres	60		
Drum diameter	Ø mm	480		
DRUM SPEED				
Extraction speed	rpm	1400		
G-Factor		530		
CONNECTION				
Electrical connection		1x230-400V 50Hz 3x400V 50Hz 1x220Vx60Hz 3x440Vx60Hz		
Electrical heating	kW	3.2		
CIRCUIT BREAKER		230V-16A/400V-10A		
WATER CONNECTION		3/4″		
DRAIN		Pump Standard drain valve available		
DIMENSIONS				
Size HxWxD	mm	850x595x585		
TRANSPORT DATA				
Gross weight - cardboard packing	kg	77		
Net weight	kg	73		
Volume (packed) - cardboard packing	m³	0.53		
Cardboard packing HxWxD	mm	915x610x660		

			ı		
TYPE		FDC112 condense	FD112 vented	FDHP112 heat pump	
CAPACITY					
Drum capacity	kg/lb	6/13			
Drum volume	litres	112			
Drum diameter	Ø mm	571x476			
CONNECTION					
Electrical connection		1x230 50Hz 3x400V 50Hz 1x220Vx60Hz 3x440Vx60Hz			
Electrical heating	kW	2.5	3	1.3	
CIRCUIT BREAKER		230V-16A 400V-10A			
AIRFLOW	m³/h	123	245	internal	
AIR EVACUATION		_	100	_	
DIMENSIONS					
Size HxWxD	mm	850x595x585			
TRANSPORT DATA					
Gross weight - cardboard packing	kg	50	45	56	
Net weight	kg	47	39	52	
Volume (packed) - cardboard packing	m³	0.53			
Cardboard packing HxWxD	mm	915x610x660			





UniMac preserves the right to change the machines and the specification in this leaflet at any

www.unimaclaundry.com