





FULL LINE FLE209E

| TYPE | Glasswasher |
|--------|--------------|
| LINE | FULL LINE |
| BASKET | 400x400 |
| SIZE | 470x535x760h |

The FULL line models represent the highest expression of technology Made in Krupps, capable of offering a total or partial replacement of clean water at each wash cycle for hygiene and brilliance never seen before. Its operation is very practical, simply remove the overflow tube to switch from partial to total replacement, with an eye always on saving. Available with various accessories, from the version with automatic water softener to the one with Acquatech System that ensures constant temperature and pressure, the Full line is the right solution for the most demanding customers. The innovative UNIKO tempered glass touch screen display makes any operation simple and intuitive, from the choice of most suitable wash cycle to its progress control, as well as constantly monitor the dishwasher state with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician thanks to the Wi-Fi IKLOUD control system that gives the possibility to act remotely to change the dishwasher parameters and resolve the situation in real-time.

The FLE209E model is equipped with Acquatech System which, through an atmospheric boiler and rinse pump, ensures constant temperature and pressure and optimum water consumption. This model is suitable for washing cups, glasses, saucers and dishes (using the appropriate basket) with always clean water and ensures a sanitising rinse cycle, proving to be the perfect choice for canteens, nursing homes, pastry shops, bakers and butchers where compliance with hygiene rules (HACCP) is essential. Separate washing and rinsing arms ensure optimum results and the tank of only 5 litres optimises consumption, thus increasing savings. The choice between 50% or 100% of water replacement makes the glasswasher extremely adaptable to your every need. The Reverse Osmosis System, the suitable detergents and the tilted basket are the answer for all premises where perfect glasses and automatic drying are indispensable elements.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the boiler from the hot water, preventing limestone forming inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all components in the front to allow easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.







| DISHWASHERS FEATURES | FULL LINE FLE209E | |
|--|---|--|
| Dimensions - (mm) L - P - H | 470x535x760h | |
| n° baskets/hour - (+55°C) | Max 40 | |
| Height glass max | 275mm | |
| Ø height plate max | 295mm | |
| Tank heating element - Tank capacity | 1,4kW - 5lt | |
| Boiler heating element - Boiler capacity | 4,5kW - 6,1lt | |
| Washing pump | 0,26kW / 0,35Hp | |
| Total power input / Current | 4,76kW / 16A - 400V3N+T 50Hz | |
| Standard input voltage | 400V3N+T 50Hz | |
| Recommended inlet water temperature | +55°C | |
| Water hardness | 7÷10 °f | |
| Water consumption per cycle (inlet suggested pressure 2 BAR) | ~5lt (total refill cycle) ~2,5lt (partial refill cycle) | |
| Adjustable detergent and rinse-aid dispenser | ELECTRIC | |
| Acquatech system rinse | si | |
| Built-in drain pump | si | |
| STANDARD EQUIPMENT | | |
| Saucer holder 12 pieces | 1 | |
| Cutlery insert | 1 | |
| Basket for glasses dim.400x400x150mm | 2 | |
| Integral tank filter | 1 | |
| OPTION | | |
| UNIKO touch display with IKLOUD Wi-Fi control | • | |
| Input voltage 230V/3+T | • | |
| Booster pump kit 0,5Hp | - | |
| Thermo/acoustic insulation double wall kit and upper cover | • | |
| Reverse osmosis system | • | |
| Inclined basket for wine glasses dim.400x400x170mm | • | |
| Kit 4 Stainless steel feet 50-70mm | • | |
| 2 baskets for glasses Ø400mm | • | |
| • INSTALLABLE ACCESSORY , - NOT INSTALLABLE ACCESSORY | | |

FLE209E



