







SOFT LINE **S208E**

TYPE	Glasswasher
LINE	SOFT LINE
BASKET	400x400
SIZE	470x595x660h

The SOFT line models are equipped with an automatic water softener that offers the possibility of breaking down the formation of limestone with extreme efficiency. In fact, the water softener is completely autonomous and automatically controls its regeneration intervals according to the hardness of the inlet water, all you have to do is fill the salt tank whenever the "no salt" message appears on the display. The resins are regenerated during wash cycles, so no machine downtime is required.

The innovative UNIKO tempered glass touch screen display makes any operation simple and intuitive, from the choice of most suitable wash cycle to its progress control, as well as constantly monitoring the dishwasher state with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician through the Wi-Fi IKLOUD control system that gives the possibility of remotely changing the dishwasher parameters and resolving the situation in real-time.

The S208E is suitable for washing cups, saucers and glasses with a clearance of up to 265 mm.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous **self-diagnosis** allows you to **minimise machine downtime**, suggesting some operations that need to be verified. The **self-cleaning cycle** at the end of the day cleans the wash tank and empties the hot water from the boiler, preventing limestone from building up inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 states that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 states that washing and rinsing begin only when the desired temperature is reached.

[H[C € €

♦WRAS









DISHWASHERS FEATURES	SOFT LINE S208E	
Dimensions - (mm) L - P - H	470x595x660h	
n° baskets/hour - (+55°C)	Max 48	
Height glass max	240mm	
Ø height plate max	265mm	
Tank heating element - Tank capacity	2,6kW - 17lt	
Boiler heating element - Boiler capacity	2,5kW - 3,2lt	
Washing pump	0,19kW / 0,25Hp	
Total power input / Current	2,79kW / 16A	
Standard input voltage	230V 50Hz	
Recommended inlet water temperature	+55°C	
Water hardness	>15 °f	
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt	
Adjustable detergent and rinse-aid dispenser	ELECTRIC	
Built-in water softener	si	
STANDARD EQUIPMENT		
Saucer holder 12 pieces	1	
Cutlery insert	1	
Basket for glasses dim.400x400x150mm	2	
Salt funnel	1	
OPTION		
UNIKO touch display with IKLOUD Wi-Fi control	•	
Booster pump kit 0,5Hp	-	
Drain pump kit 40W	•	
Reverse osmosis system	-	
Inclined basket for wine glasses dim.400x400x170mm	•	
Kit 4 Stainless steel feet 50-70mm	•	
2 baskets for glasses Ø400mm	•	
INSTALLABLE ACCESSORY , T NOT INSTALLABLE ACCESSORY		

S208E





