



SOFT LINE S540E

TYPE	Front-loading dishwasher
LINE	SOFT LINE
BASKET	500x500
SIZE	585x660x815h

The **SOFT** line models are equipped with an **automatic water softener** that offers the possibility of breaking down the formation of limestone with extreme efficiency. In fact, the water softener is completely **autonomous** and automatically controls its regeneration intervals according to the hardness of the inlet water; all you have to do is fill the salt tank whenever the “no salt” message appears on the display. The resins are regenerated during wash cycles, so no machine downtime is required.

The innovative UNIKO tempered glass touch screen display makes any operation simple and intuitive, from the choice of most suitable wash cycle to its progress control, as well as constantly monitoring the dishwasher state with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician through the Wi-Fi IKLOUD control system that gives the possibility of remotely changing the dishwasher parameters and resolving the situation in real-time.


With the **S540E** dishwasher you can wash glasses of different shapes and sizes and 18 dishes per cycle with max Ø of 350mm thanks to the baskets provided, with a maximum productivity of 40 baskets/hour (720 dishes/hour). The drain pump option allows you to handle the drain automatically and perform a partial replacement of clean water at each wash cycle.


The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous **self-diagnosis** allows you to **minimise machine downtime**, suggesting some operations that need to be verified. The **self-cleaning cycle** at the end of the day cleans the wash tank and empties the hot water from the boiler, preventing limestone from building up inside. The standard **double peristaltic electric rinse-aid and detergent dispenser** ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the **moulded washing and rinsing arms** ensure great reliability and durability. The **Thermo-stop** function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of **AISI 304 s**


DISHWASHERS FEATURES		SOFT LINE S540E
Dimensions - (mm) L - P - H		585x660x815h
n° baskets/hour - (+55°C)		Max 40
Height glass max		320mm
Ø height plate max		350mm
Trays		NO
Tank heating element - Tank capacity		2,6kW - 26lt
Boiler heating element - Boiler capacity		2,5kW - 7,3lt
Washing pump		0,52kW / 0,7Hp
Total power input / Current		3,12kW / 16A
Standard input voltage		230V 50Hz
Recommended inlet water temperature		+55°C
Water hardness		>15 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)		2,0lt
Adjustable detergent and rinse-aid dispenser		ELECTRIC
Built-in water softener		si
STANDARD EQUIPMENT		
Cutlery insert		2
Basket for glasses dim.500x500x100mm		1
Basket for 18 dishes dim.500x500x100mm		1
Salt funnel		1
OPTION		
UNIKO touch display with IKLOUD Wi-Fi control		●
Booster pump kit 0,5Hp		●
Drain pump kit 40W		●
Thermo/acoustic insulation double wall kit and upper cover		●
Stainless steel tank filter kit for rack dishwasher 500x500		●
Reverse osmosis system		-
Basket for trays with 4 compartments dim.500x500x200mm		●
Inclined basket for wine glasses dim.500x500x170mm		●
Kit 4 Stainless steel feet 50-70mm		●


● INSTALLABLE ACCESSORY , - NOT INSTALLABLE ACCESSORY

S540E



 230V+T 3,12kW
L=1900 (SCHUKO)

 G 3/4" M
L=1200

 Ø25x30
L=1500